

**CESSNA AIRCRAFT COMPANY
MODEL 300 SERIES
CONTINUED AIRWORTHINESS PROGRAM**

TITLE **Wiring Installation - Wing**

MODEL	EFFECTIVITY	INSPECTION COMPLIANCE	
T303 310 Thru T310R 320 Thru 320F	T30300001 Thru T30300315 607, 35549 Thru 310R2140 623, 658, 320-0001 Thru 320F0045	INITIAL	1000 HRS OR 2 YRS
335 336	335-0001 Thru 335-0065 633, 636, 336-0001 Thru 336-0195	REPEAT	1000 HRS OR 2 YRS Thereafter
337 Thru T337H-SP T337G Thru P337H F337E/FT337F FT337GP/FT337HP 340 Thru 340A	337-0002 Thru 33701955 P3370001 Thru P3370356 F3370001 Thru F33700055 FP33700001 Thru FP33700023 340-0001 Thru 340A1817		

PURPOSE

To inspect for possible deterioration after an extended period of time.

INSPECTION INSTRUCTIONS

1. Remove all inspection plates, open all access doors along wing, and open up wing root area (both left and right wings).
2. Remove components as necessary to allow inspection of all wiring in both wings.
3. Inspect condition of wiring and sleeving, wire supports, etc.
4. Check for any wire abrasion against sheet metal surfaces and assure that all wiring is secured properly.
5. Check electrical connectors for any sign of contact corrosion, security of contacts and condition of wiring at contacts.

ACCESS/LOCATION

Wing

DETECTABLE CRACK SIZE

N/A

INSPECTION PROCEDURE

Visual

REPAIR/MODIFICATION

Replace wiring as required.

COMMENTS